



Load it up. This versatile loader tractor gets after **ANYTHING.**



The New Tier 4i 5600 Series.

It has a nose for what you want it to do.

Visibility is key in loader work. Our MF5609 and MF5610 each offer a new sloped nose to improve sightline down the hood and beyond the bucket. The Visio roof further improves forward visibility, even at full loader height.



The larger, 6-post cab design provides a sweeping 360° view, as well as a roomier, more comfortable and productive workspace.



Powerful and maneuverable, these tractors are multi taskers, even in close quarters. The proven Dyna 4™ transmission has many new features, including AUTO DRIVE, which automatically and smoothly shifts gears as if driving a car.

| Model | 5609 | 5610 |
|------------------------------------|------------------------------------------------------------------------------------------|----------------|
| PTO power @ 2,200 rpm HP (kW) | 70 (52) | 75 (56) |
| Engine power HP (kW) | 90 (67) | 100 (75) |
| Engine make/model | 33 AWI HD by AGCO Power | |
| Cylinders/displacement L (CID) | 3-cylinder/3.3 (201) | |
| Aspiration/charge cooling | Turbocharged & intercooled | |
| Fuel system | Common rail direct injection | |
| Emissions control | External Exhaust Gas Recirculation (EGR), Diesel Oxidation Catalyst (DOC) | |
| Fuel capacity gal. (L) | 42 (160) | |
| Transmission | | |
| Type: standard | Dyna-4 transmission with speed matching; AUTO-DRIVE is optional | |
| Speeds | 4 gears, 4 ranges, 16 total speeds | |
| Shuttle | Electro hydraulic via LH 3-function control lever or optional RH factory loader joystick | |
| Creeper | Optional 14:1 reduction | |
| Rear 3-point Hitch | | |
| Type/ASAE category | Electronic linkage control with lower link draft sensing/Cat II | |
| Lift capacity @ 24" lbs. (kg) | 7,100 (3,220) | |
| 4wd Front Axle | | |
| Type | Center Drive with planetary reduction | |
| Drive engagement | Electro hydraulic | |
| Rear Axle | | |
| Type | Flange with internal wet disc brakes | |
| Differential lock | Fully locking electro hydraulic | |
| Braking | Independent, internal wet multi-disc brakes | |
| Power Take Off (PTO) | | |
| Type | Independent, electronically engaged | |
| Speeds | 540/540e | 540/540e/1,000 |
| Hydraulics | | |
| System type | Open center | |
| Standard flow at remotes gpm (Lpm) | 15 (57) | |
| Optional flow at remotes gpm (Lpm) | 26 (100) with Twin Flow System | |
| Rear remote valves | 2 standard, up to 4 available | |
| Loader joystick option | Integrated factory loader joystick with shuttle control and mid valves | |
| Operator's Area | | |
| Type of operator's area | 6-post cab, twin doors, flat deck | |
| Steering /seat | Adjustable steering/mechanical or air suspended seat | |
| Cab suspension | Optional mechanical system | |
| Dimensions | | |
| Height over cab in. (mm)* | 108.5 (2,755) | |
| Overall length in. (mm) | 167.5 (4,253) | |
| Wheelbase in. (mm) | 97.1 (2,467) | |
| Min. width at fenders in. (mm) | 79.3 (2,013) | |
| Weight lbs. (kg) | 2wd: 8,426 (3,822) /4wd: 8,978 (4,072) | |

*Height for standard cab, no susp, flat floor and 16.9R34 tires



MASSEY FERGUSON is a worldwide brand of AGCO.