

## 1500 Series specifications

WHEEL RAKES		VERTICAL FOLD MODELS		
MODEL	1508	1510	1512	
<b>Dimensions and Weights</b>				
Transport width: ft. (m)	8.5 (2.6)	9.6 (2.9)	10.6 (3.2)	
Overall length: ft. (m)	13 (4.0)	15.6 (4.8)	18 (5.5)	
Weight: lbs. (kg)	1,125 (510)	1,275 (578)	1,440 (653)	
Raking widths: ft. (m)	3 positions from 16 to 20 (4.1 to 6.1)	3 positions from 18 to 22 (5.5 to 6.7)	3 positions from 20 to 24 (6.1 to 7.3)	
Windrow widths: in. (mm)	Variable from 48 to 72 (1,219 to 1,829)			
<b>Mainframe</b>				
Raking positions	3			
Frame fold	Hydraulic			
Tire size	ST175/80D13			
Gauge wheels: in. (mm)	12 (305)	15 (381)	6:70 X 15	
<b>Finger Wheels</b>				
Number	8	10	12	
Overall diameter: in. (mm)	55 (1,397)			
Tines per wheel	40			
Tine diameter: in (mm)	0.3 (7)			
Rake wheel bearings	Tapered roller bearings with dust covers			
Flotation	Dual-wheel flotation			
Lift	Single cylinder – both sides			
<b>Tractor Requirements</b>				
Minimum horsepower: HP (kW)	25 (19)	25 (19)	30 (22)	
Hydraulics	One single-acting remote valve (hydraulic fold)			
<b>Optional Kits</b>				
Optional accessory kits are available. Please contact your local Massey Ferguson dealer.				