

3900 Series and 5000 Series specifications

WHEEL RAKES		HIGH-CAPACITY MODELS		
MODEL	3983	3986	3995	
Dimensions and Weights				
Transport width: ft. (m)	8 (2.4)	8.1 (2.5)	8.5 (2.6)	
Overall length: ft. (m)	24.6 (7.5)	27.3 (8.4)	34 (10.4)	
Weight: lbs. (kg)	3,500 (1,587)	3,800 (1,723)	5,000 (2,268)	
Raking widths: ft. (m)	0 to 24 (0 to 7.3)	0 to 28 (0 to 8.5)	25 to 35 (7.5 to 9.6)	
Windrow widths: in. (mm)	Variable from 38 to 58 (965 to 1,473)	Variable from 38 to 58 (965 to 1,473)	Variable from 38 to 61 (965 to 1,549)	
Mainframe				
Raking positions		Infinitely variable		
Frame fold		Hydraulic		
Tire sizes: in. (mm)	P205-75 X 15	P205-75 X 15	6:70 X 15	
Gauge wheels: in. (mm)	12 (305)	15 (381)	6:70 X 15	
Finger Wheels				
Number	12	14	18	
Overall diameter: in. (mm)		55 (1,397)		
Tines per wheel: in. (mm)		40		
Tine diameter		0.3 (7)		
Rake wheel bearings		Tapered roller		
Flotation		Wheels pivot independently		
Lift		Single-acting cylinder per side		
Tractor Requirements				
Minimum horsepower: HP (kW)	30 (22)	40 (30)	65 (48.5)	
Hydraulics	One double-acting remote and one single-acting remote			
Optional Kits				
Optional accessory kits are available. Please contact your local Massey Ferguson dealer.				

HEAVY-DUTY MODEL		
5130		
	12.3 (3.7)	
	28.3 (8.6)	
	5,800 (2,631)	
	Up to 30.3 (9.2)	
	Up to 72 (1.8)	
	Infinitely variable	
	Hydraulic	
	9.5L x 15	
	NA	
	17	
	60 (1,524)	
	36	
	NA	
	Tapered roller	
	One spring per wheel	
	Double-acting lift cylinder per side	
	65 (48.5)	
	One double-acting remote and one single-acting remote	