



Bigger, better tedders for BIGGER,
better hay operations.

Introducing two new expansive tedders that will cover any field faster.

As the size of commercial hay farms and custom hay operations increase, so do your demands for faster drying and more efficient tedding. We're answering with two new smartly-designed, commercial grade tedders in our TD Series: a 33' 6" eight-rotor and 41' 8" ten-rotor tedder. So next harvest, you can have more quality hay faster than ever before. To learn more, visit your dealer or masseyferguson.us.

Model	TDI655	TDI665
Transport	Chassis	Chassis
Rotors	8	10
Working width: ft. (m)	33' 6" (10.2)	41' 8" (12.7)
Transport width	9' 10"	9' 10"
Transport length	15' 8"	18' 4"
Tine arms per rotor	6	6
Tine length	16"	16"
Tine saver	Standard	Standard
Rotor speed	189 rpm	189 rpm
Rotor tires	6 x 16/6.50-8 2 x 18/8.50-8	8 x 16/6.50-8 2 x 18/8.50-8
Chassis tires	10.0/80-12	10.0/75-15.3
Power requirement	54 HP	90 HP
Hydraulic requirement	1 SAV	2 DAV
PTO speed	540 rpm	540 rpm
Drive protection	Radial pin clutch	Radial pin clutch
Weight: lbs.	3,696	4,410



Rotor head

Every TD Series tedder rotor head is built to hang tough harvest after harvest. The induction-hardened rotor casting is break-resistant and designed for even the most adverse tedding conditions.



Super C coil tines

Our exclusive Super C coil tines feature six full windings per tine to make them tough, elastic and durable. They're also mounted to the bottom of the tine arm. The result is better deflection and reduced crop build-up.



Transport chassis

Our two larger tedders (TDI655 and TDI665) are equipped with a convenient transport chassis. It allows rotors to be lifted off the ground in a vertical position and supports them, giving you improved maneuverability in and out of fields, and faster transport speeds up to 30 mph.