


IS[®] 6200

The IS6200 brings Ferris[®] back into the high horsepower diesel market for the municipal/institutional and rural groundskeeping markets. Powered by a Cat[®] 48 hp* turbo diesel engine on a 72" deck, this unit will mow easily in the toughest conditions.

THE FERRIS[®] ADVANTAGE



▶ 3" COLOR DISPLAY SCREEN

Interactive onboard computer that maintains and monitors the performance and operation of the mower.



▶ iCD[™] CUTTING SYSTEM

Every component works together to achieve superior cut quality at higher speeds. With a 2-belt deck, engineered to extend belt life and reduce downtime.



▶ SMOOTH INDEPENDENT OPERATION

Patented suspension technology enables you to mow uneven terrain faster with a consistent, quality cut - allowing you to cut more grass for increased productivity.



1 **Patented suspension system**

Utilizes rear swing-arms and front control arms with large adjustable coil-over shocks to minimize caster chatter

2 **Cat 1.7L turbo diesel engine**

This mower operates at peak performance while being powered by a 48 hp* turbo diesel engine

3 **iCD Cutting System with 2-belt deck**

Comes standard with a 72" cutting deck along with Hercules[™] II cast-iron spindles

4 **Hydraulic deck lift**

Foot activated hydraulic deck lift system for easy lifting and lowering

5 **Heavy-duty clutch & gear box**

A hand-operated 450 ft lbs Warner Electric[®] clutch and a right angled Curtis[®] gearbox with dual 1" shafts allowing you to harness more horsepower for a smoother and faster operation

6 **Transmission**

Dual-commercial 21 cc Hydro-Gear[®] pumps and 20.6 cu in Parker[®] wheel motors with an external oil cooler

7 **Long-lasting comfort**

Comes standard with the next generation rops, suspension seat and IS front suspension for an added layer of comfort

*Power level rated by engine manufacturer.



	IS6200
Part #	5901849
Engine Brand	CAT® diesel
Power Rating (gross hp*)	48
Displacement (cc)	1700
PTO	Electric
Cylinders	3
Starter	Electric
Oil Guard™ System	N/A
Fuel Tank Capacity (gal)	15
MOWER DECK	
Cutting Width (in.)	72
Cutting Height (in.)	1.5 - 6
Spindles	Hercules™ II Cast-iron
Deck Construction	iCD™ Cutting System, 2-belt
SUSPENSION & DRIVE TRAIN	
Suspension	Independent front control arms with large adjustable coil-over-shocks and a rear swing-arm with large adjustable coil-over shocks
Transmission	Dual 21cc hydro pumps and 20.6 cu in wheel motors with external oil cooler
Drive Axles (in)	1.25 Tapered
Caster Tires (in)	13 x 6.5-6 flat-free
Drive Tires (in)	26 x 12-12
SPEED	
Speeds-Fwd (mph)	0-12
Speeds-Rev (mph)	0-6
DIMENSIONS	
Overall Length (in)	89.66
Overall Width (in)	86/73.5
Deflector Down/Up	
Dry Weight (lbs)	2,518
OPERATOR SYSTEMS	
Seat Package	Premium high-back suspension seat with arm rests
ROPS	105° foldable
Instrumentation	Digital display
Controls/Safety Group	Seat activated engine kill, clutch safety switch, neutral and parking brake safety circuit, adjustable twin steering controls
Parking Brake/Safety Circuit	Hand operated external drum type brake
WARRANTY**	
Engine	2-Year limited manufacturer's warranty
Balance of Machine	4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coil-over-shocks and all suspension related components are covered for 5 years (60 months) unlimited hours. Coverage on other components varies, please see operator's manual for complete details.

Products may vary from images shown.

* Power level rated by engine manufacturer.

** See operator's manual or dealer for complete warranty details. Refer to engine operator's manual for engine warranty.

BRIGGS&STRATTON, LLC
Milwaukee, WI 53201-0702 USA
(414) 259-5333
Copyright ©2020. All rights reserved.